

It's almost ten years since Prima S.r.l. created a specific division dedicated to the world of Contract and to experts who always more often seek fabrics, which, in addition to the design, the lines and the colors, can comply with the worldwide regulations in terms of resistance, abrasion resistance and washability.

Olimpo 1 goes into this direction: 100% Trevira CS[®], engineered to provide a natural fiber look as the viscose-linen, with all the strength and resistance insured by the use of a technical and high performance yarn.

Olimpo 1 is easy to clean, can be washed in water at 40°C and it's suitable for uses where the application of fire retardant and high resistance are strictly required.

Art. OLIMPO 1 - 100 % TREVIRA CS / FR / IMO



TEST	NORME				
Weight	/	395 gr/m ²			
Width	/	140 cm			
Abrasion Martindale	UNI EN ISO 12947	40.000 rubs			
Seam Slippage	BS 2543	Warp: 4 mm Weft: 4 mm			
Pilling	UNI EN ISO 12945-2	4 (2000 rubs)			
Colour Fastness Dry Rubbing	UNI EN ISO 105-X12	Staining	5	4/5	4/5
		Colour change	4/5	4/5	4/5
Colour Fastness Wet Rubbing	UNI EN ISO 105-X12	Staining	4/5	4	3/4
		Colour change	4	4	4
Light Fastness	UNI EN ISO 105-B02	Blue scale	4/5	5	5
Flammability	UNI 8456 - 9174 - CLASS 1 - ITALIAN FIRE SAFETY CLASSIFICATION - PASS CERTIFICATE TREVIRA N°131299 DIN 4102 - B1 BS EN 1021.1 : 1994 - SOURCE 0 - CIGARETTE TEST - PASS BS EN 1021.2 : 1994 - SOURCE 1 - BUTANE FLAME - PASSED ON FR FOAM IMO 2010 FTP CODE PART 8: PASS				