

Prima S.r.l. is pleased to offer its customers a classic collection, inspired by the themes of the mountains and the Alps, but reviewed in a contemporary and modern way. Characteristic and evocative motifs are combined with the use of yarns with a technical and functional content, in order to give Stelvio collection versatility and easy use and maintenance.

The use of flame retardant, modacrylic and wool polyester yarns allows Stelvio collection fabrics to reach the standards set by the UNI 8456 - 9174 - Class 1 - Italian Fire Safety Classification. Thus, these fabrics are perfect for environments where the strict standards of the contract market are required.

To complete the collection and to give it exclusivity, here is the article Firestone CS, a piece dyed item, consisting of a precious chenille in 100% Trevira CS..

The above mentioned undisputed flame retardant qualities are enriched by an easy maintenance and the possibility of machine washing at 30° C.

The Stelvio collection is available in five color groups with a modern and contemporary taste, as well as in different patterns (plain, stripe, check and jacquard) to meet all the needs, even the most sought after.

STELVIO COLLECTION



Article	Design	Composition	Repeat (+/-3%)		Weight gr/m2	Width cm	Martindale UNI EN ISO 12947 rubs	Seam Slippage UNI EN ISO 13936-2		Pilling UNI EN ISO 12945-2 /	Light Fastness UNI EN ISO 105-B02			Colour Fastness to Rubbing UNI EN ISO 105-X12	
			vert	hor				warp	weft		light	med	dark	dry	wet
Stelvio 16	JT1084 JT1120	48% MA-34%WO-18% PL	22,8	17,5	390	140	20.000	3mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio 17	JT1088 JT1274	48% MA-34%WO-18% PL	16,8	18	390	140	20.000	4mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio 18	JT1279 JT1280	48% MA-34%WO-18% PL	10	9	495	140	20.000	4mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio 19	JT1063 JT1281	48% MA-34%WO-18% PL	4,5	4,5	450	140	20.000	4mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio stripe 14	JT1354 JU0280	48% MA-34%WO-18% PL	22	7,5	395	140	20.000	4mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio mini 8	JT1059	48% MA-34%WO-18% PL	1,5	1,5	405	140	20.000	4mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio plain 5	JT1115	48% MA-34%WO-18% PL	/	/	336	140	20.000	4mm	3mm	3/4	4/5	5	5	4/5	3/4
Firestone CS	RU0108	100% Trevira CS	/	/	505	140	50.000	3mm	3 mm	5	4/5	5	5	4/5	3/4
Stelvio plain 1	J10740	48% MA-34%Wo-18% PL	/	/	345	140	20.000	3mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio plain 3	J10872	48% MA-34%Wo-18% PL	/	/	335	140	20.000	3mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio pois 3	J10483	48% MA-34%Wo-18% PL	2,3	2,5	415	140	20.000	3mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio 4	J10838	48% MA-34%Wo-18% PL	56,5	35	355	140	20.000	3mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio 5	J10840	48% MA-34%Wo-18% PL	8,9	6,2	355	140	20.000	3mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio mini 2	J10841	48% MA-34%Wo-18% PL	3,7	3	355	140	20.000	4mm	3mm	3/4	4/5	5	5	4/5	3/4
Stelvio stripe 2	J10844	48% MA-34%Wo-18% PL	49,5	35	355	140	20.000	3mm	4,5mm	3/4	4/5	5	5	4/5	3/4
Stelvio stripe 3	J10950	48% MA-34%Wo-18% PL	17	/	340	140	20.000	3mm	4,5mm	3/4	4/5	5	5	4/5	3/4

Stelvio Articles Flammability: UNI 8456 - 9174 - CLASS 1 - ITALIAN FIRE SAFETY CLASSIFICATION PASS

Firestone CS Flammability: CLASSE 1, UNI 8456 (1987)
EN 1021-1 / EN 1021-2
NFP 92-507 : M1 FRANCE